



Pluricode 300


4" Thermal Transfer Label Printer

Cod. STTTPC001



MAIN SPECIFICATIONS

- Direct thermal and thermal transfer printing applications
- High printing speed(5IPS), fast label throughput
- Double type sensors allowing to support broad range of labels
- Dual-wall frame, robust and sturdy structure
- TPH special designed overcoat, endure large printing volume
- ZPL and TSPL programming language
- Bundled with Bartender label designer software & Seagull Windows Driver



**300-meter
Ribbon Capacity**



Logistic



Medical



Retail



Healthcare



Barcode



Security



Hospitality
& Leisure



Windows



Manufacturing

Pluricode is a trademark of Pluriservice Spa

Via F. Santi, 22 - Z.Ind. Bassette 48123 Ravenna (RA) - Tel. +39 0544 456669 - Fax +39 0544 688954

Social capital fully paid: 1.000.000,00 € - commerciale@pluriservice.it



Pluricode 300

4" Thermal Transfer Label Printer

Cod. STTTPC001



PRINTING

Printing Method: Thermal transfer/Direct thermal
Resolution: 203dpi(8dots/mm)
Printing Speed: 5IPSMAX
Printing Width: 108mm Max
Printing Length: from 15mm

PROCESSOR

32 bit RISC CPU

MEMORY

RAM: 32 MB
Flash: 16 MB

DETECTION

Sensors: Adjustable reflective sensor, Fixed transmissive sensor (Central aligned), Head-up sensor, Ribbon end sensor

MEDIA

Types: Roll-fed or Fan-fed, Die-cut or Continuous label, Tag stock, Continuous receipt paper
Width: 0.79"(20mm) – 4.65"(118mm)
Thickness: 0.003"(80um) – 0.007"(180um)
Label Roll Diameter: 5"(127mm)
Core Diameter: 1"(25.4mm), 1.5"(38mm), 3"(76.2mm)

RIBBON

Types: Wax, Wax/Resin, Resin
Width: 1.33"(33.8mm) – 4.33"(110mm)
Length: 984'(300m)
Core Diameter: 1"(25.4mm)

PROGRAMMING LANGUAGE: TSPL, ZPL Simulation

SOFTWARE

Label Design: Bartender UltraLite
Driver: Windows 2000, XP, Vista 7, 8, 10 By Seagull

RESIDENT FONTS

Bitmap Fonts: 8, 12, 16, 24, 32 and OCR A & B
90°, 180°, 270° rotatable. 10 times maximum expandable in horizontal and vertical directions.
TTF fonts: Monotype CG Triumvirate™ scalable true type font
Bitmap fonts: 90°, 180°, 270° rotatable, single characters 90°, 180°, 270° rotatable

DOWNLOAD FONTS

TTF fonts: 90°, 180°, 270° rotatable
Asian fonts: 16x16, 24x24. Traditional Chinese, Simplified Chinese, Japanese, Korean

CODE PAGES: 39

BARCODE

1D: 20
2D: PDF417, Maxicode, DataMatrix, QR Code, Aztec

INTERFACES

Standard: USB, RS232C, Ethernet

CONTROL PANEL

Two bi-color status LEDs: Ready, Status
Control key: Feed

POWER ADAPTER

AC/DC switching power adapter
I/P: AC100-240V, 50/60Hz, 0/P:
DC 24V/2.5A, peak 7A

ENVIRONMENT

Operation: 41°F(5°C)-104°F(40°C)
30%-85%, non-condensing
Storage: -4°F(-20°C)-122°F(50°C)
10%-90%, non-condensing

PHYSICAL CHARACTERISTICS

Dimension(L*W*H): 285*226*171mm
Weight: 2.26kg, excluding consumables

OPTIONS

External label roll holder for 8"
(203mm) OD label rolls

AGENCY APPROVALS FCC, CE

Pluricode is a trademark of Pluriservice Spa

Via F. Santi, 22 - Z.Ind. Bassette 48123 Ravenna (RA) - Tel. +39 0544 456669 - Fax +39 0544 688954
Social capital fully paid: 1.000.000,00 € - commerciale@pluriservice.it