



2D Barcode Scanner Cordless

Pluricode

323BT

Cod. LTMNGM002



SCAN PERFORMANCE

Processor type: 32Bit
Scan mode: handheld
Memory: 16MB
Alarm mode: Red light alarm, Buzzer alarm
Resolution: 640(horizontal) x 480(vertial),256 gray levels
Scan angle: 45°(horizontal); 30°(vertical)
Scan speed: 250mm/sec
Scan depth of field:
5 mil(Code 39) 90~120mm
13 mil(UPC/EAN) 30~305mm
20 mil(Code 39) 30~450mm
PDF417(10mil) 50~225mm
Datamatrix(10mil) 52~240mm
Barcode type: Australian Post, Aztec, BPO, Canada Post, Codabar, Codablock, Code 11, Code 39, Code 93, Code 128/EAN128, DataMatrix, Dutch Post, EAN.UCC Composite, Interleaved 2 of 5, Japan Post, Matrix 2 of 5, MaxiCode, MicroPDF417, MSI Code, PDF417, Planet, Plessey Code, Postnet, QR code, RSS, Standard 2 of 5, Telepen, TLC 39, UPC/EAN

ELECTRICAL

Voltage: DC+5V±5%
Operating current: 60mA(working); 40mA(standby); 300mA(operating)
Interfaces: Bluetooth 4.0, 2.4G ,USB
Communicate distance: Bluetooth 30m (in vacant space)
Light level: Visible Red light 630+10nm

ENVIRONMENTAL

Operating temperature: -20 °C ~60°C
Storage temperature: -30 °C ~70°C
Humidity: 5% to 95% (Non-condensing)
Light environment: The normal direct sunlight indoor and outdoor
Drop: Designed to withstand 1.8m drops
IP degree: IP54

PHYSICAL

Dimensions (LxWxH): 170mm×100mm×75mm
Weight: 150g (without cable)
Material: ABS+EVA
Color: black
Accessories: scanner, manual, USB cable, 2.4G adapter

Pluricode is a trademark of Pluriservice Spa

Via F. Santi, 22 - Z.Ind. Bassette 48123 Ravenna (RA) - Tel. +39 0544 456669 - Fax +39 0544 688954
Social capital fully paid: 1.000.000,00 € - commerciale@pluriservice.it